



UHF Stick Reader R830

Applications

- Desktop Readers / Encoders
- Access Control
- Logistics

Features

- High-speed data transfer
- Integrated antenna
- Full SDK
- Optional HID

RFID Options

- **UHF** (EPC C1 GEN2 / ISO18000-6C)

Description

Stick Reader R830 is a small, handy and simple UHF RFID Reader with integrated antenna. Its USB 2.0 interface guarantees high-speed data transfer. R830 Stick Reader supports ISO18000-6C tags incl. EPC Class1 Gen2.

Thanks to its frequency band from 865 to 928 MHz, the UHF Pen Stick Reader complies with the ETSI & FCC standard. It is perfect for desktop or identification applications.

The R830 comes with full SDK (reader host protocol, DLL, source code) and MS Windows based demo software. Hardware based HID is optional.

Technical Data

Electrical Specifications

Power Supply	5 VDC via USB
Power Consumption	< 350 mA
Operating Frequency	865 – 928 MHz (ETSI & FCC)
Max. Power	+20dBm / 100mW (software adjustable)
Operating Distance	Up to 15 cm (depending on type of transponder)
Built-in Antenna	Linear polarized
Interface	USB 2.0

Mechanical Specifications

Dimensions	80 x 21 x 12 mm
------------	-----------------

Environmental Conditions

Operating Temperature	-20°C ... +50 °C
Humidity	5 % to 95 %

Supported Standards / Tags

Standard ISO 18000-6C (EPC Class 1 Generation 2)

SDK Information

Supported Languages C++, C#, Java, .net

*Reading distance depends on tag, antenna and environmental conditions

Order Codes

Version	Order Code
Basic Version	OEM-UHF-R830-USB-SR01
HID Version	OEM-UHF-R830-USB-SR01-HID
TTL Version	OEM-UHF-R830-TTL-SR01

iDTRONIC GmbH
Donnersbergweg 1
67059 Ludwigshafen
GERMANY

Phone +49 (0) 621 66 90 09 4-0
Fax +49 (0) 621 66 90 09 4-9
E-Mail: info@idtronic-rfid.com
Web: idtronic-rfid.com

For further information & prices, please contact info@idtronic-rfid.com

Subject to alteration without prior notice
©2018 iDTRONIC GmbH